BATTERY DATA SHEET



NiMh | ROBOT

REF BSH-HU05





The BSH range is a complete range of batteries for robotic mowers specially designed for intensive charge and discharge use. Equipped with high-quality, high-capacity NiMh cells, this range thus offers the robot great autonomy in working.

FEATURES

- Compatible battery type
- High cycle life: up to 500 cycles
- Long battery life: capacity sometimes higher than the original
- High quality NiMH cells
- · More than 200 models of robots covered

DIMENSIONS & WEIGHT

215±1mm Length: Width: 67.65±1mm 22.70±2mm Height: Weight: 0.85kg (tolerance ±3%)

APPLICATIONS



COMPATIBILITY (LIST NOT EXHAUSTIVE)

HUSQVARNA 220AC/230ACX/265ACX

SPECIFICATIONS

Nominal voltage:	18V (SC - 15S1P)
Energy:	39.6Wh
Nominal capacity:	2.2Ah
Technology:	NiMh
Brand cells:	-
Protection function (PCM):	-
Standard charge	
Max charge Current:	1.5A (24V max)
Standard discharge Standard discharge current: Max discharge current:	0.6A (cut-off voltage: 12V) 1.5A
Operationg temp. range Charge temperature:	0°C to 45°C
Discharge temperature:	-10°C to 60°C
Storage temperature:	0°C to 40°C

TERMINALS

