BATTERY DATA SHEET



VOLTAGE

ENERGY

CAPACITY

LITHIUM | ROBOT



The BSL range is a complete range of batteries for robotic mowers specially designed for intensive charge and discharge use. Equipped with high-quality, high-capacity Lithium cells, this range thus offers the robot great autonomy in working.

FEATURES

- Compatible battery type
- High cycle life : up to 500 cycles
- Long battery life: capacity sometimes higher than the original battery
- High quality Lithium cells (LG, Samsung, Panasonic,...)
- More than 200 models of robots covered

DIMENSIONS & WEIGHT

Length:	69±1mm
Width:	56±1mm
Height:	67±2mm
Weight:	0.25kg (tolerance ±3%)
Weight	0.20kg (toterunite 20%)

APPLICATIONS



COMPATIBILITY (LIST NOT EXHAUSTIVE)

- HUSQVARNA Automower 105/305/308
- MCCULLOCH R600, R800, R1000 (2007-2019)
 GARDENA
 - R38Li, R40Li, R80Li

SPECIF	FICATIONS
Nominal voltage:	18V (18650 - 5S1P)
Energy:	36Wh
Nominal capacity:	2.0Ah
Technology:	Lithium-ion
Brand cells:	SAMSUNG - INR18650 - 20R
Protection function (PCM):	-
Standard charge Max charge Current:	1A (the output voltage must be less than 21V)
Standard discharge	
Standard discharge current:	0.4A (cut-off voltage must be higher than 12.5V)
Max discharge current:	15Á

36_{wh}

2.0Ah

Operationg temp. range Charge temperature: Discharge temperature: Storage temperature:

REF BSL-HU01







0°C to 45°C -10°C to 60°C

0°C to 40°C

sales@bs-battery.com